

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2004 (06.05.2004)

PCT

(10) International Publication Number
WO 2004/038409 A2

(51) International Patent Classification⁷: **G01N 33/487**

(21) International Application Number:
PCT/EP2003/015044

(22) International Filing Date: 28 August 2003 (28.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02/10663 28 August 2002 (28.08.2002) FR

(71) Applicant (for all designated States except US): **COM-
MISSARIAT A L'ENERGIE ATOMIQUE** [FR/FR];
31/33, rue de la Fédération, F-75752 Paris 15ème (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PICOLLET-DA-
HAN, Nathalie** [FR/FR]; Le Crozat, F-38580 La Ferrière
(FR). **CAILLAT, Patrice** [FR/FR]; 10 rue de Provence,

F-38130 Echirolles (FR). **REVOL-CAVALIER, Frédéric**
[FR/FR]; 11 rue de la Saulne, F-38180 Seyssins (FR).
CHATELAIN, François [FR/FR]; 413 rue Hector
Berlioz, Le Chevallon de Voreppe, F-38340 Voreppe (FR).
SAUTER, Fabien [FR/FR]; 22 rue Sisteron, F-38170
Seyssinet-Pariset (FR).

(74) Agent: **BRYKMAN, Georges**; c/o BREVATOME, 3, rue
du Docteur Lancereaux, F-75008 Paris (FR).

(81) Designated States (*national*): CN, JP, US.


(84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: DEVICE FOR MEASURING THE ELECTRICAL ACTIVITY OF BIOLOGICAL ELEMENTS AND ITS APPLICATIONS



(57) Abstract: The invention relates to a device for measuring the electrical activity of biological elements, comprising a substrate (12) which has lower and upper faces and at least one through opening (120), said opening being delimited by a set of walls, and characterized in that: it comprises two plates (11, 13) placed on either side of the lower and upper faces of the substrate and delimiting with said set of walls a chamber (19); each of the plates is provided, on its face lying opposite the substrate, with at least one electrode (110, 130) facing the opening in the substrate; each of the plates further has at least one channel that starts inside said chamber and connects the latter to the outside of the device; and the chamber communicates with the outside of the device only through said channels.